

The INLINE T5 Series

These **Save It Easy**® units are designed to give trouble-free retrofit of high efficiency T5 linear fluorescent tubes into existing standard T8 and T12 fixtures.

Standard T8 FTL and Fixture	Type of T8 FTL and its operating power with Electromagnetic Ballast	Type of T5 high efficiency FTL used with Save It Easy ® and its operating power	Power Saved	% Energy Saved
2 feet T8 (590mm)	18W 27W	Inline T5 14W 16.5W	10.5W	38%
2 feet T12 (590mm)	20W 30W	Inline T5 14W 16.5W	13.5W	45%
4 feet T8 (1200mm)	36W 46W	Inline T5 28W 30.0W	16.0W	34%
4 feet T12 (1200mm)	40W 49W	Inline T5 28W 30.0W	19.0W	38%
5 feet T8 (1500mm)	58W 72W	Inline T5 35W 39.0W	33.0W	45%
5 feet T12 (1500mm)	65W 78W	Inline T5 35W 39.0W	39.0W	50%
6 feet T8 (1800mm)	70W 84W	Inline T5 49W 53.0W	31.0W	37%
6 feet T12 (1800mm)	75W 95W	Inline T5 49W 53.0W	42.0W	44%

INLINE T8 Units

These **Save It Easy**® units are designed to make possible the retrofit of shorter high efficiency T8 fluorescent tube lamps into existing 8 feet T12 fixtures.

Standard T8 and T12 FTL and Fixture	Type of T8 FTL and its operating power with Electromagnetic Ballast	Type of T8 FTL used in combination with various types of Save It Easy ® and its operating power	Power Saved	% Energy Saved
8 feet T12 (2400mm)	125W 175W	Inline T8 70W 77.0W	98.0W	56%