

# The INLINE T5 Series

These **Save It Easy**® units are designed to give trouble-free retrofit of high efficiency T5 linear fluorescent tubes into existing standard T8 and T12 fixtures.

Standard T8 FTL and Fixture	Type of T8 FTL and its operating power with Electromagnetic Ballast		Type of T5 high efficiency FTL used with <b>Save It Easy</b> ® and its operating power		Power Saved	% Energy Saved
2 feet T8 (590mm)	18W	27W	Inline T5 8.5W	11W	16W	59%
2 feet T12 (590mm)	20W	31W	Inline T5 8.5W	11W	20W	65%
4 feet T8 (1200mm)	36W	46W	Inline T5 24W	28W	18W	39%
4 feet T12 (1200mm)	40W	50W	Inline T5 24W	28W	22W	44%
5 feet T8 (1500mm)	58W	71W	Inline T5 35W	39W	33W	45%
5 feet T12 (1500mm)	65W	78W	Inline T5 35W	39W	39W	50%
6 feet T8 (1800mm)	70W	84W	Inline T5 49W	53W	31W	37%
6 feet T12 (1800mm)	75W	95W	Inline T5 49W	53W	42W	44%

# INLINE T8 Units

These **Save It Easy**® units are designed to make possible the retrofit of shorter high efficiency T8 fluorescent tube lamps into existing 8 feet T12 fixtures.

Standard T8 and T12 FTL and Fixture	Type of T8 FTL and its operating power with Electromagnetic Ballast		Type of T8 FTL used in combination with various types of <b>Save It Easy</b> ® and its operating power		Power Saved	% Energy Saved
8 feet T12 (2400mm)	125W	175W	Inline T8 70W	77W	98W	56%